

GENERAL INFORMATION

Before product selection, we recommend reading the following technical sheet:

[IG 01 - GENERAL INFORMATION LISTONE GIORDANO](#)



LISTONE GIORDANO® ATELIER RESERVE

3-layers hardwood floor collection made of a top layer in Oak wood species with a core in Poplar battenboard and a counterbalanced layer in Oak wood species.

SPECIFICATIONS

PRODUCT	WIDTH***	LENGTH**	TOTAL THICKNESS	TOP LAYER*	SUPPORT	FITTING SYSTEMS	WEIGHT
Réserve Traccia	190 mm	1600 and 1900 mm	18,0 mm	3,5 mm	batten support counterbalanced	glued / floating	11,6 Kg/m ²
Réserve Mareggiata	190 mm	1600 and 1900 mm					
Réserve Mareggiata	260 mm	1800 and 3000 mm					

* Listone Giordano® Traccia and Mareggiata products feature an uneven top layer after the surface processing and the thickness may be reduced in some areas compared to the one above mentioned.
In the Listone Giordano® Mareggiata the top layer thickness may be reduced up to 1 mm in some areas.

** The products are supplied in one length or random lengths, according to availability.
The material supplied may incorporate up to 10% of shorter lengths compared to those mentioned in the specifications

***The handcrafted nature of the processes and treatments performed on these products means that the final result may differ from batch to batch, both in terms of surface and hue.
In the case of matching several widths, the material supplied is likely to feature uneven hues.

To verify the availability of the various versions of Listone Giordano® products, consult the current Price list.

All the products of the collection Listone Giordano® Atelier Réserve comply with the requirements of the European Norm UNI EN 13489:2018 "Wood-flooring and parquet - Multi-layer parquet elements".

PATTERNS

The stack bond or aligned straight lay is always possible with every Listone Giordano® product but it is needed to communicate this choice when ordering

OTHER TECHNICAL INFORMATION

TOP-SUPPORT LAYER GLUING	Conforms to the requirements of the <i>class D4 of the UNI EN 204 regulation</i>
PROFILE	Interlocking tongues and grooves on 4 sides Bevelled on all 4 edges

GRADES

Listone Giordano® Atelier Réserve products are available in the following grades

- Esprit (Réserve)

To know the necessary information about grades see the appropriate sheet:

[**GC 01 - GRADES LISTONE GIORDANO**](#)



FINISHES AND SURFACE PROCESSING

Listone Giordano® Atelier Réserve products are available with the following finishes:

- Invisible Touch
- Oleonature

and with the following surface processing:

- Traccia
- Mareggiata

To know the necessary information about finishes and surface processing see the appropriate sheet:

[**FP 01 - FINISHES AND SURFACE PROCESSING LISTONE GIORDANO**](#)



INSTRUCTIONS FOR INSTALLATION

The installation of the Listone Giordano® Atelier Réserve products can be glued down or floating according to the indications in the table at page 1.

To know the necessary information about laying see the appropriate sheet:

[**DL 01 - INSTRUCTIONS FOR INSTALLATION LISTONE GIORDANO**](#)



CLEANING, USE AND MAINTENANCE

The Listone Giordano® Atelier Réserve product finishes need specific cleaning and maintenance, in accordance with appropriate instructions to be taken into account.

To know the necessary information about cleaning, use and maintenance see the appropriate sheet:

[**CM 01 - CLEANING, USE AND MAINTENANCE LISTONE GIORDANO**](#)



CERTIFICATIONS



BIOSPHERA

Biosphera is a marking system based upon Listone Giordano®'s green procurement policy to provide consumers with brief, clear and useful information on the origin of raw materials. Many products of the collection Listone Giordano® offer both in their top layer and in their support the *Biosphera certified* mark that identifies raw materials whose forestry management is certified according to recognized standards at the international level (FSC®, PEFC, SFI, OLB, LEI, etc.) or the *Biosphera controlled* mark that identifies raw materials whose legal sourcing and forestry management, although not yet certified, is backed up by specific audit and related papers.



PEFC

Chain-of-Custody Certification, which guarantees that products are sourced from sustainably, managed forests.



CE MARK

All the products of the collection Listone Giordano® strictly comply to all CE rules regarding hardwood floors.



TOY CERTIFICATION

All the Listone Giordano® finishes are approved according to standard EN71-3 which assures fitness for use in children's toys.



AIR EMISSIONS

French certification of Emissions of Volatile Organic Compounds. All Listone Giordano® products tested according to n°2011-321 French Decree have attained A+ rating, the highest among those in the Decree.



FORMALDEHYDE

All the products of the collection Listone Giordano® comply to the class E1, which is amongst the strictest European regulations (UNI EN 14342).



ANTI-BACTERIAL FINISH CRYSTALCARE

All the XPlus2, NaturPlus2, NaturPlus2 Matt, MattPlus, Invisible Touch and Oleonature finishes are antibacterial certified by CATAS S.p.a. laboratories according to ISO 22196:2007 regulation.



ISO 9001

Quality Management System certification.



ISO 14001

Environmental Management System certification for the Miralduolo di Torgiano (PG) factory.

ISO 45001

Certification of Occupational Health and Safety Management System.

MADE IN

All the products of the collection Listone Giordano® are Made in Italy.



FIRE REACTION CERTIFICATION

In the following table, you can find fire reaction classes of the various products:

PRODUCT	FINISH	FIRE REACTION CLASS <small>(according to the requirements of the EN14342 regulation on the CE mark)</small>
Réserve Traccia / Filo di lama / Mareggiata	Invisible Touch	Dfl-s1
	Oleonature	Fire proof oil: Cfl-s1 Oleonature: Dfl-s1

Cfl-s1 class for glued down installation is valid in case of gluing on non-combustible substrate; it is also valid in case of gluing, using Ecolfit® Listone Giordano®, on underlay 4 mm thick composed of fibres and granules of SBR compacted by a polyurethane adhesive (mass per area unit $2,9 \pm 0,2 \text{ kg/m}^2$) in a hot process, itself glued on non-combustible substrate using Ecolfit® Listone Giordano®.

Cfl-s1 class for floating installation is valid in case of installation on underlay IsoDrum Top Isolmant loose-laid on non-combustible support.

TS 03 – October 2023